

# Table of Contents

<b>JQuery Coding Standards.....</b>	<b>1</b>
Shorthands.....	1
Wrap \$.....	1
Global variables.....	1
Propagating perl settings to javascript.....	1
The foswiki object.....	1
Avoid Internet Explorer errors.....	2
Metadata.....	2
LiveQuery.....	2

# JQuery Coding Standards

Follow Drupal's JavaScript coding standards

## Shorthands

Use the jQuery shorthand `$` where possible:

```
$(function() { ... });
```

instead of

```
$(document).ready(function() { ... });
```

## Wrap `$`

If you want to use jQuery's `$` variable, wrap your code like this:

```
(function($) {  
    // code using $ variable  
})(jQuery);
```

## Global variables

If you want to use global variables within the scope of your code, wrap your code like this:

```
(function() {  
    var foo = 'bar'; // yay, it's almost like I'm global  
})();
```

If you want to use global variables in the global scope, put the variable in the `foswiki` namespace:

```
foswiki.foo = 'bar';
```

Mind the predefined global variables. See next section.

## Propagating perl settings to javascript

The `jquery.foswiki` plugin will initialize the global `foswiki` object with a set of variables that are created by reading `meta` tags in the HTML header. These have the format

```
<meta name="foswiki.foo.bar.baz" content="string/boolean/object/function" />
```

## The `foswiki` object

This will create the appropriate sub-namespaces and initialize the named property with the value in the `content` attribute.

There is a set of predefined variables that can be used in your javascript code via the `foswiki` namespace:

Name	Content
foswiki.web	%WEB%
foswiki.topic	%TOPIC%"
foswiki.scriptUrl	%SCRIPTURL%
foswiki.scriptUrlPath	%SCRIPTURLPATH%
foswiki.pubUrl	%PUBURL%
foswiki.pubUrlPath	%PUBURLPATH%
foswiki.systemWebName	%SYSTEMWEB%
foswiki.usersWebName	%USERSWEB%
foswiki.wikiName	%WIKINAME%
foswiki.loginName	%USERNAME%
foswiki.wikiUserName	%WIKIUSERNAME%
foswiki.serverTime	%SERVERTIME%
foswiki.ImagePluginEnabled	%IF{"context ImagePluginEnabled" then="true" else="false"}%
foswiki.MathModePluginEnabled	%IF{"context MathModePluginEnabled" then="true" else="false"}%

## Avoid Internet Explorer errors

- Use an object if you need an associative array, not an array. [source]
- Declare all local variables with `var` before they are used.
- Remove trailing commas from array and object definitions, i.e.:

```
var object = { foo: 'bar' }
```

not

```
var object = { foo: 'bar', }
```

## Metadata

Use JQueryMetadata to integrate jQuery plugins into Foswiki.

## LiveQuery

Use JQueryLiveQuery to initialize your plugin for all html elements of a page. Otherwise content that is loaded asynchronously using ajax won't be initialized. LiveQuery will take care of that automatically.

Instead of

```
$(".jqPluginName").each(function() {
  // initializer
});
```

use

```
$(".jqPluginName").livequery(function() {
  // initializer
});
```

See JQueryMetadata for a more thorough example of using metadata and livequery

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions

- . System
  
- Log In
  
- **Toolbox**
  - Users
  - Groups
  - Index
  - Search
  - Changes
  - Notifications
  - RSS Feed
  - Statistics
  - Preferences
  
- **User Reference**
  - BeginnersStartHere
  - TextFormattingRules
  - Macros
  - FormattedSearch
  - QuerySearch
  - DocumentGraphics
  - SkinBrowser
  - InstalledPlugins
  
- **Admin Maintenance**
  - Reference Manual
  - AdminToolsCategory
  - InterWikis
  - ManagingWebs
  - SiteTools
  - DefaultPreferences
  - WebPreferences
  
- **Categories**
  - Admin Documentation
  - Admin Tools
  - Developer Doc
  - User Documentation
  - User Tools
  
- **Webs**
  - Public
  - System

- 
- 



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback