Table of Contents

package Telecoms.....1
ClassMethod new().....1
ObjectMethod phone($who).....1

package Telecoms

ClassMethod new()

ObjectMethod phone($who)

must be called something like this

```
my $mobile = new Telecoms();
$mobile->phone( "home" );
```

or you can pass the object in as a parameter if you need to:

```
Telecoms::phone( $mobile, "home" );
```

Related Topics: ClassMethod, StaticMethod

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions

Topic revision: r1 - 12 Sep 2009 - 03:24:39 - ProjectContributor

- . System
- Log In

- **Toolbox**
- Users
- Groups
- Index
- Search
- Changes
- Notifications
- RSS Feed
- Statistics
- Preferences

- **User Reference**
- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**
- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**
- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**
- Public
- System

Copyright © by the contributing authors. All material on this site is the property of the contributing authors.
Ideas, requests, problems regarding Wiki? Send feedback