Table of Contents

VarENV.....1
ENV{"varname"} -- inspect the value of an environment variable.....1

VarENV

You are here: Wiki >System Web>VarENV (09 Jan 2009, ProjectContributor)EditAttach

ENV{"varname"} -- inspect the value of an environment variable

- Returns the current value of the environment variable in the CGI (Common Gateway Interface) environment. This is the environment that the CommandAndCGIScripts are running in.
- **Note:** For security reasons, only those environment variables whose names match the regular expression in `{AccessibleENV}` in the **Security Settings/Miscellaneous** section of `configure` can be displayed. Any other variable will just be shown as an empty string, irrespective of its real value.
- Example: `%ENV{MOD_PERL}%` displays as: not set
- If an environment variable is undefined (as against being set to the empty string) it will be returned as `not set`.
- Related: HTTP_HOST, REMOTE_ADDR, REMOTE_PORT, REMOTE_USER

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions

Topic revision: r1 - 09 Jan 2009 - 13:00:00 - ProjectContributor

- . System

- Log In

- **Toolbox**
- Users
- Groups
- Index
- Search
- Changes
- Notifications
- RSS Feed
- Statistics
- Preferences

- **User Reference**
- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**
- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**
- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**
- Public
- System

Copyright © by the contributing authors. All material on this site is the property of the contributing authors.
Ideas, requests, problems regarding Wiki? Send feedback