

Table of Contents

VarMETA.....	1
META -- displays meta-data.....	1

VarMETA

You are here: Wiki >System Web>VarMETA (09 Jan 2009, ProjectContributor)EditAttach

META -- displays meta-data

- Provided mainly for use in templates, this macro generates the parts of the topic view that relate to meta-data (attachments, forms etc.) The `formfield` item is the most likely to be useful to casual users.
- Syntax: `%META{ "item" ... }%`
- Parameters:

Item	Options	Description
"formfield"	<code>name="...":</code> name of the field. The field value can be shortened as described in FormattedSearch for <code>\$formfield</code> <code>newline="...":</code> by default, each newline character will be rewritten to <code>
</code> to allow metadata that contains newlines to be used in tables, etc. <code>\$n</code> indicates a newline character. <code>bar="...":</code> by default, each vertical bar is rewritten to an HTML entity so as to not be mistaken for a table separator.	Show a single form field
"form"	<i>none</i>	Generates the table showing the form fields. See Form Definition
"attachments"	<code>all="on"</code> to show hidden attachments. <code>title="..."</code> to show a title - only if attachments are displayed. <code>template="..."</code> to use a custom template for the rendering of attachments; default <code>attachtables</code> is used.	Generates the list of attachments
"moved"	<i>none</i>	Details of any topic moves
"parent"	<code>dontrecurse="on":</code> By default recurses up tree, this has some cost. Equivalent to <code>depth=1</code> <code>depth="...":</code> Return only the specified ancestor. <code>nowebhome="on":</code> Suppress WebHome. <code>prefix="...":</code> Prefix that goes before parents, but only if there are parents, default <code>" "</code> . <code>format="...":</code> Format string used to display each parent topic where <code>\$web</code> expands to the web name, and <code>\$topic</code> expands to the topic name; default: <code>" [[\$web.\$topic] [\$topic]] "</code> <code>suffix="...":</code> Suffix, only appears if there are parents; default <code>" "</code> . <code>separator="...":</code> Separator between parents; default <code>" > "</code> .	Generates the parent link

- Related: METASEARCH

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions

- . System
- Log In
-
- **Toolbox**
 - Users
 - Groups
 - Index
 - Search
 - Changes
 - Notifications
 - RSS Feed
 - Statistics
 - Preferences
-
- **User Reference**
 - BeginnersStartHere
 - TextFormattingRules
 - Macros
 - FormattedSearch
 - QuerySearch
 - DocumentGraphics
 - SkinBrowser
 - InstalledPlugins
-
- **Admin Maintenance**
 - Reference Manual
 - AdminToolsCategory
 - InterWikis
 - ManagingWebs
 - SiteTools
 - DefaultPreferences
 - WebPreferences
-
- **Categories**
 - Admin Documentation
 - Admin Tools
 - Developer Doc
 - User Documentation
 - User Tools
-
- **Webs**
 - Public
 - System



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? [Send feedback](#)