Table of Contents

VarSERVERTIME.....1
SERVERTIME{"format"} -- formatted server time.....1

VarSERVERTIME

You are here: Wiki >System Web>VarSERVERTIME (09 Jan 2009, ProjectContributor)EditAttach

SERVERTIME{"format"} -- formatted server time

- Same format qualifiers as `%GMTIME%`
- Syntax: `%SERVERTIME%` OR `%SERVERTIME{"format"}%`
- `%SERVERTIME%` uses the Date format defined as {DefaultDateFormat} in configure
- Example: `%SERVERTIME{"$hou:$min"}%` expands to `04:42`
- **Note:** When used in a template topic, this macro will be expanded when the template is used to create a new topic. See TemplateTopics#TemplateTopicsVars for details.
- Related: GMTIME, SERVERTIME

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions

Topic revision: r1 - 09 Jan 2009 - 13:00:00 - ProjectContributor

- . System

- Log In

- **Toolbox**
- Users
- Groups
- Index
- Search
- Changes
- Notifications
- RSS Feed
- Statistics
- Preferences

- **User Reference**
- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**
- Reference Manual
- AdminToolsCategory

- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**
- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**
- Public
- System

Copyright © by the contributing authors. All material on this site is the property of the contributing authors.
Ideas, requests, problems regarding Wiki? Send feedback